

# Approved product certificate

No.: 05842-1

X-Module A/S, Test lab. Facility, Lilleringvej 24, 8462 Harlev

Product licenced to: X-Module A/S, Lilleringvej 14, DK-8462 Harlev

Product manufactured by: X-Module A/S, Lilleringvej 24, DK-8462 Harlev J

Applicant of testing: Mr. Steen Kreiberg  
Date of testing: 29.05.2018  
Certificate file reference: HSC/SBK/Testlab/3819.0199  
Date of issue: 01.06.2022  
Valid until: 31.05.2024

Test facility:



Signature:

A handwritten signature in blue ink, appearing to be "S. Kreiberg".

## Product description - dimensions:

- Single square truss system: "X-15 EXPOWIRE" 05xxx (Reg. trademark) (Pat. ped, EUR design)
- Dimensions: Square truss 150 x 150 mm (outer dimensions).
- Cord members:  $\varnothing$  20 mm
- Bracing members:  $\varnothing$  8 mm
- Truss units lengths: 0,15 - 2,4 m

## Product description - materials:

- Supportive elements: Aluminium AlMgSi0,5
- Truss elements: 30% fibre reinforced composite.

## Product components tested according to:

- DIN 4113; ISO 527-1/-2

## Flammability:

- The products qualify for DIN 4102 – B1; ISO 1210/UL94-VO

## Additional information:

- Truss units assembled with connecting element (connector) or cubic connecting element (cube) is disregarded by test.
- Single individual units only.

## Load data, structure:

- Allowable normal force on main cord: 250 N
- Allowable normal force on bracing members: 25 N

## Load data, Truss units:

Truss length (m)	Undistributed load (Kg)	Distributed load (Kg)
0,6	100	100
1,2	100	100
1,8	100	100
1,95	75	100

- Modules must be connected to verticals in both ends.
- Max. free span 6,0 m.
- Spans must be supported at both ends.
- Loads are in addition to self weight loads.
- Only use standard connectors for truss.
- Load table only applies to simple beam load case.